



## ► INFLATABLES

	CLASSIC MARK 1		CLASSIC MARK 2C		CLASSIC MARK 2	
	HD	ST	HD	ST	HD	ST
<b>DIMENSIONS (METERS - FEET/INCHES)</b>						
Overall length	3,5 - 11'6"		3,8 - 12'6"		4,2 - 13'9"	
Inside length	2,3 - 7'7"		2,55 - 8'4"		2,95 - 9'8"	
Overall width	1,61 - 5'3"		1,83 - 6'0"		1,83 - 6'0"	
Inside width	0,77 - 2'6"		0,92 - 3'0"		0,92 - 3'0"	
Buoyancy tube diameter	0,425 - 1'5"		0,455 - 1'6"		0,455 - 1'6"	
<b>CAPACITY</b>						
Passengers (ISO)	5	5	6	6	7	7
Maximum payload <sup>1</sup> (kg - lbs)	590 - 1300,7	590 - 1300,7	750 - 1653,5	750 - 1653,5	840 - 1851,9	840 - 1851,9
Total weight (kg - lbs)	64 - 141,1	61 - 134,5	77 - 169,8	74 - 163,1	87 - 191,8	83 - 183,0
Airtight compartments	3 + 1	3 + 1	3 + 1	3 + 1	3 + 1	3 + 1
<b>DESIGN CATEGORY</b>						
European directive N° 94/25/CE	C	C	C	C	C	C
<b>OUTBOARD DATA</b>						
● Short shaft ■ Long shaft	●	●	●	●	●	●
Minimum recommended power <sup>2</sup> (Hp)	6	6	8	8	10	10
Minimum recommended power <sup>2</sup> (kW)	5	5	6	6	8	8
Maximum recommended power <sup>2</sup> (Hp)	20	20	25	25	30	30
Maximum recommended power <sup>2</sup> (kW)	15	15	19	19	23	23
Maximum power allowed <sup>3</sup> (Hp)	25	25	35	35	40	40
Maximum power allowed <sup>3</sup> (kW)	19	19	26	26	30	30
Maximum weight of outboard <sup>4</sup> (kg - lbs)	70 - 154,3	70 - 154,3	85 - 187,4	85 - 187,4	95 - 209,4	95 - 209,4
Maximum speed <sup>5</sup> (km/h - mph)	45 - 28,0	45 - 28,0	50 - 31,1	50 - 31,1	54 - 33,6	54 - 33,6
<b>DIMENSIONS OF THE FOLDED BOAT (METERS - FEET/INCHES)</b>						
Length of 1st bag	1,3 - 4'3"	1,3 - 4'3"	1,44 - 4'9"	1,44 - 4'9"	1,44 - 4'9"	1,44 - 4'9"
Width of 1st bag	0,6 - 1'12"	0,6 - 1'12"	0,65 - 2'2"	0,65 - 2'2"	0,68 - 2'3"	0,68 - 2'3"
Height of 1st bag	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"	0,35 - 1'2"
Length of 2nd bag	0,89 - 2'11"	0,89 - 2'11"	1,05 - 3'5"	1,05 - 3'5"	1,05 - 3'5"	1,05 - 3'5"
Width of 2nd bag	0,6 - 1'12"	0,6 - 1'12"	0,61 - 2'0"	0,61 - 2'0"	0,65 - 2'2"	0,65 - 2'2"
Height of 2nd bag	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"	0,14 - 0'6"

All dimension measurements indicated have a tolerance of +/- 3%. Weight and speed measurements have a tolerance of +/- 5%.

(1) The maximum payload rating has been calculated according to ISO standards. Operating at or near maximum payloads is only advised in calm water and at reduced speeds.

(2) The spread of engine sizes corresponds to the efficient use of the boat with an average load. The minimum power is exploitable in relaxed activities, such as fishing, while the maximum recommended power is destined for performance activities such as water-skiing. For additional information all Zodiac boats from 10'2"/3.10 m to 13'9"/4.20 m can plane with 2 people on board (total load of 310 lbs/140 kg) using only a 6-8 /5-6 kW outboard.

(3) Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boats for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(4) Maximum authorized weight: dry weight, according to the engine manufacturer's catalogue specifications.

(5) Maximum speeds are given only as a general guide to understanding boat performance. They have been established by experienced professional pilots in ideal navigating conditions with one person aboard. Boat speed will be affected by the make of the motor, boat load, propeller and the water and weather conditions.



## EQUIPMENT LIST

HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	MAIN OPTIONAL ACCESSORIES
<ul style="list-style-type: none"><li>• Choice of floor :<ul style="list-style-type: none"><li>- Quick fit aluminium floorboards with tie-down rail system (Classic HD)</li><li>- Marine plywood floorboards in an aluminium frame with tie-down rail system (Classic ST)</li></ul></li><li>• Inflatable keel</li><li>• Aluminium engine support plate</li><li>• 2 self-bailers</li></ul>	<ul style="list-style-type: none"><li>• Strongan™ Duotex™ 2 x 1100 decitex fabric</li><li>• Semi-recessed valves</li><li>• Polyamid lacing cuff and safety grab lines</li><li>• Large profile spray deflecting rubbing strake</li><li>• 1 bow handle</li><li>• 4 carrying handles</li><li>• 2 stainless steel towing rings</li><li>• Reinforced cone ends</li></ul>	<ul style="list-style-type: none"><li>• Removable bow bag</li><li>• Fittings for optional forward steering cross-bar</li><li>• Launching wheels fitting kit</li><li>• Mast and pennant</li><li>• 2 carrying bags</li><li>• 2 paddles</li><li>• Foot pump</li><li>• 1 pressure gauge</li><li>• Repair kit</li><li>• Owner's manual</li></ul>	<ul style="list-style-type: none"><li>• 1 adjustable bench</li><li>• Double deluxe seat with locker box (except Mark 1)</li><li>• Inflatable double seat</li><li>• Overall cover</li><li>• Fishing rod holder</li><li>• Launching wheels</li><li>• Trolley</li><li>• Electric pump</li><li>• Remote steering unit</li><li>• Bathing ladder</li></ul>