



► RIB TENDERS

	340DL	380DL	420DL	470DL	530DL
DIMENSIONS (METERS - FEET/INCHES)					
Overall length	3,4 - 11'2"	3,8 - 12'6"	4,2 - 13'9"	4,7 - 15'5"	5,3 - 17'5"
Inside length	2 - 6'7"	2,4 - 7'11"	2,8 - 9'2"	2,98 - 9'9"	3,68 - 12'1"
Overall width	1,77 - 5'10"	1,77 - 5'10"	1,86 - 6'1"	2,05 - 6'9"	2,24 - 7'4"
Inside width	0,86 - 2'10"	0,86 - 2'10"	0,94 - 3'1"	1,05 - 3'5"	1,2 - 3'11"
Buoyancy tube diameter	0,455 - 1'6"	0,455 - 1'6"	0,455 - 1'6"	0,5 - 1'8"	0,52 - 1'8"
CAPACITY					
Passengers (ISO)	4	5	6	9	9
Maximum payload ¹ (kg - lbs)	605 - 1333,8	735 - 1620,4	850 - 1873,9	945 - 2083,4	1115 - 2458,2
Total weight (kg - lbs)	193 - 425,5	218 - 480,6	273 - 601,9	390 - 859,8	400 - 881,9
Airtight compartments	3	3	3	5	5
DESIGN CATEGORY					
European directive N° 94/25/CE	C	C	C	C	C
OUTBOARD DATA					
Shaft: ● Short ■ long ✖ Extralong ✱ Ultralong ▲ Jet	■	■	■	■	■
Minimum recommended power ² (Hp)	15	20	30	50	40
Minimum recommended power ² (kW)	12	15	23	38	30
Maximum recommended power ² (Hp)	30	30	50	70	75
Maximum recommended power ² (kW)	23	23	38	53	56
Maximum power allowed ³ (Hp)	30	40	50	90	115
Maximum power allowed ³ (kW)	23	30	38	68	87
Maximum weight of outboard ⁴ (kg - lbs)	100 - 220,5	110 - 242,5	120 - 264,6	170 - 374,8	195 - 429,9
Maximum speed ⁵ (km/h - mph)	48 - 29,8	54 - 33,6	60 - 37,3	68 - 42,3	70 - 43,5
HULL STORAGE DIMENSIONS (METERS - FEET/INCHES)					
Length	3,18 - 10'5"	3,58 - 11'9"	3,98 - 13'1"	4,34 - 14'3"	4,73 - 15'6"
Width	1,11 - 3'8"	1,11 - 3'8"	1,25 - 4'1"	1,38 - 4'6"	1,54 - 5'1"
Height	0,96 - 3'2"	0,96 - 3'2"	1,03 - 3'5"	1,14 - 3'9"	1,7 - 5'7"
Hull angle	18°	18°	18°	21,5°	24,5°

All dimension measurements indicated have a tolerance of +/- 3%. Weight and speed measurements have a tolerance of +/- 5%.

(1) The maximum payload rating has been calculated according to ISO standards. Operating at or near maximum payloads is only advised in calm water and at reduced speeds.

(2) The spread of engine sizes corresponds to the efficient use of the boat with an average load. The minimum power is exploitable in relaxed activities, such as fishing, while the maximum recommended power is destined for performance activities such as water-skiing. For additional information all Zodiac boats from 10'2"/3.10 m to 13'9"/4.20 m can plane with 2 people on board (total load of 310 lbs/140 kg) using only a 6-8 Hp/5-6 kW outboard.

(3) Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boats for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(4) Maximum authorized weight: Dry weight, according to engine manufacturers catalogue's specifications. Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boat for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(5) Maximum speeds are given only as a general guide to understanding boat performance. They have been established by experienced professional pilots in ideal navigating conditions with one person aboard. Boat speed will be affected by the make of the motor, boat load, propeller and the water and weather conditions.



EQUIPMENT LIST

HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	MAIN OPTIONAL ACCESSORIES
<ul style="list-style-type: none"> • V-shaped fibreglass hull with built-in flaps (deep V on 470 and 530) • Moulded non-skid deck (self-draining when empty on 530) • Anchor locker with upholstered seat • Rear locker with gas strut (plywood floor on 530) • Lateral locker (420 / 470 / 530) • 1 bow D-ring • 2 stern rings • 1 self-bailer 	<ul style="list-style-type: none"> • Sharc™ Duotex™ 2 x 1100 decitex fabric • Removable tube system • Semi-recessed valves • 2 exterior handles • Large profile rubbing strake (XL on 530) • Reinforced cone ends • Interior handles (2 on 340 / 380, 4 on 420 / 470 / 530) 	<ul style="list-style-type: none"> • Stainless steel bow rail • Steering console with : <ul style="list-style-type: none"> - Steering + steering system + cable - 3 breakers (7 on 530) - Cup beverage holder (530) - Glove box - Windscreen + grab handle (530) • Built-in fuel tank + gauge + fuel/water separator <ul style="list-style-type: none"> - 35 litres / 9.2 US gal (340 / 380) - 57 litres / 15 US gal (420) - 85 litres / 22.5 US gal (470) - 120 litres / 31.7 US gal (530) • Recess for extinguisher • Double pilot/co-pilot seat with removable upholstered seat and collapsible backrest (340 / 380 / 420 / 470) • Double pilot/co-pilot seat with removable upholstered seat and collapsible backrest + bolster (530) • Passenger seats with removable upholstered cushion • Aft sundeck with upholstery (530) • 3 stainless steel mooring cleats • 3 lifting points (4 on 530) • Courtesy light • Navigation lights • 12-volt plug (470 / 530) • Battery switch • Battery box • Automatic bilge pump • Telescopic bathing ladder (530) • 2 paddles • Foot pump • Valve cap pressure gauge • Repair kit • Owner's manual 	<ul style="list-style-type: none"> • Lifting slings kit • Overall cover • Sundeck (420 / 470 / 530) • Shower kit with 50 litres / 13.2 US gal fresh water tank (530) and 26 litres / 6.8 US gal (470) • Roll-bar (530) • Picnic table (470 / 530) • Ski mast (420 / 470 / 530) • Side bathing ladder (340 / 380 / 420 / 470) • Canvas hood (420 / 470 / 530) • Synthetic teak deck • Central stainless steel mast with water-skiing ring and white navigation lights (530)